

PARTNER 58-R / 58-U Thermal Printers

FEATURES:

- Small size and elegant design
- Can drive cash drawer
- High printing speed
- Compatible with ESPON
- Printing head life: 50KM



SPECIFICATIONS:

Printing Method	Direct thermal
Print Density	384dots/line (203DPI)
Character Size	384dots/line, ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Barcode Types	JAN13(EAN13) JAN8(EAN8) CODE39
Printing Command	Compatible with EPSON ESC/POS
Language	Buyer language support
Printing Speed	90mm/sec
Paper Width	57.5±0.5mm
Paper Thickness	0.06-0.08mm
MTBF(life)	50km
Dimension	190*132*119mm
Gross Weight	1.2KG
Sensors	Paper Near End Sensor, Paper End Sensor, Cover open sensor
Roll Paper	Φ75mm
Interface	RS-232 (model 58-R), USB (model 58-U)
Driver	Win XP, Win Vista, Win 7, Win 8 compatible with ESPON
Adapter Voltage Input	AC 110V/220V, 50-60Hz
Adapter Voltage Output	DC12V/3A
Printer Input Voltage	DC12V/3A
Cash Drawer Control	DC12V/1A
Working Temperature	0-45degree C, Humidity: 10-80%
Saving Temperature	-10-60degree C, Humidity: 10-90%
Certificate	CE/FCC/CCC/RoHS